



Tipo/Type	CMV G REBE	CMV 4G RE BE	CMV 6G RE BE	CMV 8G RE BE	CMV 12G RE BE
N° prese / Fastening Points		4	6	8	12
Portata / Capacity		400 kg	600 kg	800 kg	1200 kg
Dim. min. lastra / Min. glass sheet dim.		780 x 780 mm	1250 x 780 mm	1250 x 780 mm	1250 x 1250 mm
Peso / Weight		ca. 160 kg	ca. 175 kg	ca. 190 kg	ca. 250 kg
Rotazione / Rotation		motorized	motorized	motorized	motorized
Basculamento / Tilting		motorized	motorized	motorized	motorized
Tensione / Voltage		220/380/ 24 V. C.C.	220/380/ 24 V. C.C.	220/380/ 24 V. C.C.	220/380/ 24 V. C.C.
Optional		Radiocomando per gestione dei movimenti a distanza Remote control for remote movements		Accensione e spegnimento del gruppo pompante Electric panel for automatic start/stop electric vacuum pump	

CMV G REBE

Gruppo pompante elettrico e motorizzazioni alimentati a richiesta:
- 380 V / 50 Hz - 220 V monofase - 24 V DC (corrente continua).
Doppio circuito del vuoto.

Doppio sistema di allarme acustico e visivo per segnalazione della diminuzione del grado di vuoto (fornito completo di carica batterie).

Doppio serbatoio di sicurezza incorporato nella struttura.

Rotazione elettrica 360° continui.

Basculamento elettrico 0-90°.

L'apparecchio è comandato a distanza attraverso una pulsantiera con cavo di lunghezza di 5 metri.

CMV G REBE

Electric pump and motors powered on request:

- 380 V/Hz - 220 V single-phase - 24 V DC

Double vacuum circuit.

Double audible and visible alarm system to warn of vacuum loss (complete with battery charger 220 V single-phase).

Double safety tank mounted on the structure.

Electric rotation 360° continuous.

Electric swivel 0-90°.

The machine is remotely controlled by a push-button panel with cable 5 mt long.